



DI6013D-1

Product Family: Dishwashers

Commercial width: 60 cm

Commercial height: 82 cm

Installation: Fully-integrated

Third upper basket for cutlery

Motor: Single phase

EAN code: 8017709184520



Programs / Functions

No. of programmes: 5

Washing temperatures: 38°, 45°, 50°, 65°, 70° °C

Soak, Rapid 27', ECO, Normal, Super

Baskets

Basket colour: Grey

Basket components colour: Grey

Upper Basket: With central fixed racks

Height adjustment of the upper basket: On two levels, by extraction

Largest loadable dish in upper basket: 23,5 cm

Lower Basket: With single foldable rack

Lower basket with anti-drip inserts

Largest loadable dish in lower basket: 30 cm

Technical Features

Controls: Electronic

Programme graphics: Symbols

On/off indicator

Salt light indicator: Light

Rinse aid indicator: Light

End of cycle indicator: Acoustic signal

Washing system: Orbital

Water softener: With electronic setting

Flood protection system: Single Acquastop

Water supply: Single; cold/hot water max. 60°C - energysave with hot water up to 35%

Max water hardness: 100°FH;58°dH

Drying system: Natural condenser drying

Steam protection: In plastic

Tub material: Stainless steel

Filter: Stainless steel

Concealed heating element

Hinges: Self balancing with fixed hinges

Min. and max. frontal panel weight: 2 - 7 kg

Adjustable feet: 7cm, from 820 to 890 mm

Insulation level: Hyper

Back cover

Depth of dishwasher with open door (mm): 1146

Back feet adjustable from front

Top cover: In plastic

Performance / Energy Label

Number of place settings: 13
 Energy efficiency class: A+
 Noise level: 48 dB(A) re 1pW
 Energy consumption per cycle (kWh/cycle): 1.01 kWh
 Water consumption per cycle (l/cycle): 12 litres
 Annual energy consumption: 292 kWh/year
 Annual water consumption: 3360 litres
 Reference programme: ECO

Total cycle time of reference programme (min): 195 min
 Energy consumption - stand by off mode: 0.02 W
 Energy consumption - stand by on mode: 0.8 W
 Duration of the stand by on mode (min): 5 min

Electrical Connection

Plug: (G) UK e Singapore
 Connected power: 1800 W
 Current: 13 A
 Voltage: 220-240 V
 Type of connection: Single-phase

Frequency (Hz): 50 Hz
 Power supply cable length: 140 cm

Accessories not included



KIT6CX

Classic aesthetics stainless steel panel with 14 mm. handle. Can be fitted on the fully integrated dishwashers.



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



KITPL60FABB

Toekick Kit in White colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPL60FABN

Toekick Kit in Black colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPL60FABX

Toekick Kit in Stainless Steel with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPLV2

Kit extension for dishwasher and washing machine: length mt. 2

