

KDD90VXE-2

Product family: Hood
Hood Type: Fully Integrated hood
Design: Fully integrated
Extraction: Extraction
Electronic control
Perimeter extraction
Material: Stainless steel
Type of steel: Brushed
EAN code: 8017709223175



Aesthetics

Colour: Black
 Decoration / Special colour: --NA--
 Finishing: Satin
 Aesthetics: Universale
 Serie: --NA--
 Collaborations: --NA--

Glass Type: Black
 Serigraphy colour: White
 Logo: Silk screen

Controls

Control setting: Touch control
 Led color: Red
 Display: Digital

Programs / Functions

No. of speeds: 4
 Intensive speed
 24h air filter function
 Time-setting options: Automatic switch-off

Technical Features

Remote motor: KITRBDD - Kit Optional
 No. of lights: 1
 Light type: LED
 Light Power: 7 W
 Dimmer mode
 Light color temperature scale (°K): 4000 °K
 Free outlet maximum capacity: 725 m³/h
 Motor power: 270 W

No. of filters: 2
 Anti-grease filters: Aluminium
 Filter replacement indicator
 Vent outlet: 150 mm

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	160	40
Speed 2	290	53

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 3	350	54
Speed 4	430	60
Intensive speed	700	70

Accessories Included

Sliding door
Tube reduction

Performance / Energy Label

Annual Efficiency Consumption (AEChood): 58.3 KWh/year
Energy efficiency class (EEC): A
Fluid Dynamic Efficiency (FDE): 30
Fluid Dynamic Efficiency class (FDEC): A
Lighting Efficiency (LE): 29 lux/W
Lighting Efficiency Class (LEC): A
Grease Filtering Efficiency (GFE): 65.1 %
Grease Filtering Efficiency Class (GFEC): D
Air flow at minimum speed (Qmin): 160 m³/h
Air flow at maximum speed (Qmax): 350 m³/h
Air flow at boost speed (Qboost): 700 m³/h
Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 40 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 54 dB(A)
Airbourne acoustical A-weighted sound power emission at

boost speed (SPEboost): 70 dB(A)
Power Consumption in Off mode (Po): 0.49 W
Time increase factor (F): 0.9
Energy Efficiency Index: 53.8
Measured air flow rate at best efficiency point (Qbep): 397 m³/h
Measured air pressure at best efficiency point (Pbep): 441 Pa
Measured electric power input at best efficiency point (Wbep): 162 W
Nominal Power consumption of the light system (WL): 7 W
Average illumination of the light on the cooking surface (Emiddle): 200 lux
Sound power level at highest setting (Lwa): 54 dB(A)

Electrical Connection

Electrical connection rating: 277 W
Voltage: 220-240 V
Frequency (Hz): 50-60 Hz
Power supply cable length: 1500 mm

Accessories not included



KITFCDD

Charcoal filter for hood Down Draft Kit 1 piece Dishwasher safe

KITRBDD

kit remote blower for DD hood

KITVEN150

No return valve diameter 150 mm



RCKF2

Remote control

