

KS9500BLE

Familie: Afzuigkap
Hood Type: Decoratieve wandkap
Design: T-vorm plat
Filtering: Exclusie
Elektronische bediening: Ja
Randafzuiging: Nee
Materiaal: Gelakt materiaal
Type roestvrijstaal: Geborsteld
EAN-code: 8017709212223
Hood width: 90 cm



Esthetiek

Kleur: Zwart
 Gedecoreerd/ Speciale kleur: --NA--
 Esthetiek: Universale
 Serie: --NA--
 Collaborations: --NA--

Logo: In reliëf

Bediening

Regeling bediening: Elektronische toetsen

Programma's / functies

Aantal snelheden: 3
 Snelheid Intensief: Ja
 Luchtzuiveringsfunctie (24 uur): Nee
 Overige functies: Nee
 Opties tijdprogrammering: Automatische uitschakeling

Overige opties: Nee
Auto-Vent: Nee

Technische specificaties

Motorloze afzuigkap: Nee
 Remote motor: Nee
 Aantal lampen: 2
 Type lamp: LED
 Vermogen lamp: 2 W
 Dimmerfunctie: Nee
 Light color temperature scale (°K): 4000 °K
 Capaciteit P0: 800 m³/h
 Vermogen motor: 275 W

No. of filters: 3
 Vetfilters: Aluminium
 Meegeleverde koolstoffilters: Nee
 Indicator vervangen filter: Ja
 Diameter ventilatie outlet: 150 mm
 Terugslagklep: Ja

	Capaciteit (IEC 61591) [m³/h]	Geluidsniveau (IEC 60704-2-13) [dB(A)]
Snelheid 1	307	53
Snelheid 2	395	58
Snelheid 3	558	67

	Capaciteit (IEC 61591) [m³/h]	Geluidsniveau (IEC 60704-2-13) [dB(A)]
Snelheid Intensief	759	73

Meegelerde accessoires

Afstandsbediening: Nee

Reductie pijp: Nee

Prestaties / energielabel

Annual Efficiency Consumption (AEChood): 54,3 KWh/year

Energy efficiency class (EEC): A

Fluid Dynamic Efficiency (FDE): 29.2

Fluid Dynamic Efficiency class (FDEC): A

Lighting Efficiency (LE): 95,9 lux/W

Lighting Efficiency Class (LEC): A

Grease Filtering Efficiency (GFE): 78,9 %

Grease Filtering Efficiency Class (GFEC): C

Air flow at minimum speed (Qmin): 307 m³/h

Air flow at maximum speed (Qmax): 558 m³/h

Air flow at boost speed (Qboost): 759 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 53 dB(A)

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A)

Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost): 73 dB(A)

Power consumption in stand-by mode (Ps): 0,49 W

Time increase factor (F): 0.9

Measured air flow rate at best efficiency point (Qbep): 376 m³/h

Measured air pressure at best efficiency point (Pbep): 449 Pa

Measured electric power input at best efficiency point (Wbep): 160 W

Nominal Power consumption of the light system (WL): 2 W

Average illumination of the light on the cooking surface (Emiddle): 211 lux

Sound power level at highest setting (Lwa): 67 dB(A)

Elektrische aansluiting

Stekker: Nee

Aansluitwaarde: 278 W

Spanning: 220-240 V

Frequentie: 50-60 Hz

Lengte voedingskabel: 1000 mm

Ook beschikbaar

Andere beschikbare kleuren: Roestvrijstaal, Crème

Codes andere beschikbare kleuren: KS9500XE - KS9500PE

Opties niet inbegrepen


Meegelerde koolstoffilters: FLT4

Terugslagklep: Nee

Kit toebehoren: Nee

Diffuser kit: Nee

Accessories not included



FLT4

Charcoal filter Kit 1 piece



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

