

KSED62XE

Familie: Afzuigkap
Hood Type: Decoratieve wandkap
Design: Trapeze
Filtering: Explosie
Elektronische bediening: Nee
Randafzuiging: Nee
Materiaal: Roestvrijstaal
Type roestvrijstaal: Geborsteld
EAN-code: 8017709201876



Esthetiek

Kleur: Roestvrijstaal
 Gedecoreerd/ Speciale kleur: --NA--
 Finishing: Geborsteld
 Esthetiek: Universale
 Serie: --NA--

Collaborations: --NA--
 Logo: In reliëf

Bediening

Regeling bediening: Slider

Programma's / functies

Aantal snelheden: 3
 Snelheid Intensief: Nee
 Luchtzuiveringsfunctie (24 uur): Nee
 Overige functies: Nee
 Opties tijdprogrammering: Nee

Overige opties: Nee
 Auto-Vent: Nee

Technische specificaties

Motorloze afzuigkap: Nee
 Remote motor: Nee
 Aantal lampen: 2
 Type lamp: Halogeen
 Vermogen lamp: 20 W
 Dimmerfunctie: Nee
 Capaciteit P0: 600 m³/h
 Vermogen motor: 200 W
 No. of filters: 2
 Vetfilters: Aluminium

Meegeleverde koolstoffilters: Nee
 Indicator vervangen filter: Nee
 Diameter ventilatie outlet: 150 mm
 Minimum distance from ELECTRIC hob: 650 mm
 Minimum distance from GAS hob: 750 mm
 Terugslagklep: Ja

	Capaciteit (IEC 61591) [m³/h]	Geluidsniveau (IEC 60704-2-13) [dB(A)]
Snelheid 1	351	53
Snelheid 2	420	57

	Capaciteit (IEC 61591) [m³/h]	Geluidsniveau (IEC 60704-2-13) [dB(A)]
Snelheid 3	635	67

Meegeleverde accessoires

Afstandsbediening: Nee

Sliding door: Nee

Reductie pijp: Nee

Prestaties / energielabel

Annual Efficiency Consumption (AEChood): 87,8 KWh/year

Energy efficiency class (EEC): C

Fluid Dynamic Efficiency (FDE): 26

Fluid Dynamic Efficiency class (FDEC): B

Lighting Efficiency (LE): 13,3 lux/W

Lighting Efficiency Class (LEC): D

Grease Filtering Efficiency (GFE): 74,4 %

Grease Filtering Efficiency Class (GFEC): D

Air flow at minimum speed (Qmin): 351 m³/h

Air flow at maximum speed (Qmax): 635 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 53 dB(A)

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax): 67 dB(A)

Time increase factor (F): 1.00

Energy Efficiency Index: 74.7

Measured air flow rate at best efficiency point (Qbep): 355 m³/h

Measured air pressure at best efficiency point (Pbep): 385 Pa

Measured electric power input at best efficiency point (Wbep): 146 W

Nominal Power consumption of the light system (WL): 40 W

Average illumination of the light on the cooking surface (Emiddle): 532 lux

Sound power level at highest setting (Lwa): 67 dB(A)

Elektrische aansluiting

Stekker: Nee

Aansluitwaarde: 240 W

Spanning: 220-240 V

Frequentie: 50-60 Hz

Lengte voedingskabel: 1500 mm

Ook beschikbaar

Andere beschikbare kleuren: Nee

Accessories not included



FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

