

KSEG7XE

Product family: Hood
Hood Type: Integrated hood
Design: Fully integrated
Extraction: Extraction
Material: Stainless steel
Type of steel: Brushed
EAN code: 8017709203368



Aesthetics

Colour: Stainless steel
Decoration / Special colour: --NA--
Finishing: Satin
Aesthetics: Universale
Serie: --NA--
Collaborations: --NA--

Serigraphy colour: Black
Logo: Silk screen

Controls

Control setting: Slider

Programs / Functions

No. of speeds: 3

Technical Features

No. of lights: 2
Light type: LED
Light Power: 4 W
Free outlet maximum capacity: 520 m³/h
Motor power: 205 W
No. of filters: 2
Anti-grease filters: Aluminium

Vent outlet: 150 mm
Minimum distance from ELECTRIC hob: 650 mm
Minimum distance from GAS hob: 650 mm

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	250	52
Speed 2	340	59
Speed 3	505	69

Accessories Included

Tube reduction

Performance / Energy Label



Annual Efficiency Consumption (AEChood): 90.7 KWh/year

Energy efficiency class (EEC): D

Fluid Dynamic Efficiency (FDE): 13.2

Fluid Dynamic Efficiency class (FDEC): D

Lighting Efficiency (LE): 13 lux/W

Lighting Efficiency Class (LEC): D

Grease Filtering Efficiency (GFE): 75.1 %

Grease Filtering Efficiency Class (GFEC): C

Air flow at minimum speed (Qmin): 250 m³/h

Air flow at maximum speed (Qmax): 505 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin): 52 dB(A)

Airborne acoustical A-weighted sound Power Emission at

maximum speed (SPEmax): 69 dB(A)

Time increase factor (F): 1.5

Measured air flow rate at best efficiency point (Qbep): 300 m³/h

Measured air pressure at best efficiency point (Pbep): 245 Pa

Measured electric power input at best efficiency point (Wbep): 155 W

Nominal Power consumption of the light system (WL): 8 W

Average illumination of the light on the cooking surface (Emiddle): 100 lux

Sound power level at highest setting (Lwa): 69 dB(A)

Electrical Connection

Electrical connection rating: 213 W

Voltage: 220-240 V

Frequency (Hz): 50-60 Hz

Power supply cable length: 1500 mm

Optional accessories

Charcoal filter: KITFC142

Non return valve: KITVENT150

Accessories not included

KITVEN150

No return valve diameter 150 mm

