

KSEG7XE

Product family: Hood

Hood Type: Integrated hood Design: Fully integrated Extraction: Extraction Material: Stainless steel Type of steel: Brushed EAN code: 8017709203368



Aesthetics

Colour: Stainless steel

Decoration / Special colour: --NA--

Finishing: Satin

Aesthetics: Universale

Serie: --NA--

Collaborations: --NA--

Controls

Control setting: Slider

Programs / Functions

No. of speeds: 3

Technical Features

No. of lights: 2 Light type: LED Light Power: 4 W

Free outlet maximum capacity: 520 m³/h

Motor power: 205 W No. of filters: 2

Anti-grease filters: Aluminium

Serigraphy colour: Black Logo: Silk screen

Vent outlet: 150 mm

Minimum distance from ELECTRIC hob: 650 mm Minimum distance from GAS hob: 650 mm

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	250	52
Speed 2	340	59
Speed 3	505	69

Accessories Included

Tube reduction

Performance / Energy Label



Annual Efficiency Consumption (AEChood): 90.7 KWh/year

Energy efficiency class (EEC): D Fluid Dynamic Efficiency (FDE): 13.2 Fluid Dynamic Efficiency class (FDEC): D

Lighting Efficiency (LE): 13 lux/W Lighting Efficiency Class (LEC): D

Grease Filtering Efficiency (GFE): 75.1 % Grease Filtering Efficiency Class (GFEC): C Air flow at minumum speed (Qmin): 250 m³/h Air flow at maximum speed (Qmax): 505 m³/h

Airbourne acouistical A-weighted sound Power Emission at

minimum speed (SPEmin): 52 dB(A)

Airborne acoustical A-weighted sound Power Emission at

maximum speed (SPEmax): 69 dB(A)

Time increase factor (F): 1.5

Measured air flow rate at best efficiency point (Qbep): 300 m³/h Measured air pressure at best efficiency point (Pbep): 245 Pa Measured electric power input at best efficiency point (Wbep): 155 W

Nominal Power consumption of the light system (WL): 8 W Average illumination of the light on the cooking surface

(Emiddle): 100 lux

Sound power level at highest setting (Lwa): 69 dB(A)

Electrical Connection

Electrical connection rating: 213 W

Voltage: 220-240 V Frequency (Hz): 50-60 Hz

Power supply cable length: 1500 mm

Optional accessories

Charcoal filter: KITFC142 Non return valve: KITVENT150

Accessories not included

KITVEN150

No return valve diameter 150 mm

