

# PM6912WLDX

**Built-in:** Traditional  
**Dimensions:** 90 cm  
**Power supply:** Mixed  
**Type:** Mixed  
**EAN code:** 8017709230500  
**Colour:** Black  
**Finishing:** Glass  
**Aesthetics:** Dolce Stil Novo  
**Serie:** --NA--  
**Material:** Glass  
**Glass Type:** Ceramic  
**Glass edge:** Straight edge  
**Glass on Steel**  
**Pan stands:** Cast iron  
**Burners:** Smeg Contemporary  
**Burners Material:** Alluminium  
**Burner Coating:** Black Ceram  
**Type of control setting:** Control knobs  
**Slider**  
**Control knobs position:** Front  
**No. of controls:** 1  
**Controls colour:** Black  
**Components finishing:** Stainless Steel  
**Serigraphy colour:** Grey  
**Alternative colours available:** Copper



## Programs / Functions

Total no. of cook zones: 5	Main on/off switch
No. of gas cook zones: 1	Power levels: 9
No. of induction cook zones: 4	
No. of cooking zones with Booster: 4	
No. of Flexible zones: 2	

## Options

Flexible Zone Type: MultiZone	End of cooking acoustic alarm
Multizone Option	Residual time indicator
Simmering Function	Show Room Demo Option
Keep warm automatic function	Control Lock / Child Safety
Melting/Low temperature cooking function	Rapid level selection
Pause option	
End cooking timer: 4	
Minute minder: 1	

## Technical Features

Centre left - Gas - UR - 6.00kW  
 Rear centre - Induction - multizone - 2.10kW - Booster 3.60kW - 18.0x23.0 cm  
 Front centre - Induction - Multizone - 2.10kW - Booster 3.60kW - 18.0x23.0 cm



Rear right - Induction - multizone - 2.10kW - Booster 3.60kW - 18.0x23.0 cm

Front right - Induction - Multizone - 2.10kW - Booster 3.60kW - 18.0x23.0 cm

Multizone center - Booster 3.60 W - 385x230 cm

Multizone right - Booster 3.60 W - 385x230 cm

Automatic setting according to pan dimension

Automatic switch off when overflow

Automatic pan detection: Yes, min 9 cm

Residual heat indicator

Permanent Automatic Pot Detection with indication of the relative control

Protection against accidental start up

Gas safety valves

Automatic Ignition

Automatic switch off when overheat

### Accessories Included

---

Cast iron wok support: 1

### Electrical Connection

---

Electrical connection rating (W): 7400 W

Current: 33 A

Voltage (V): 220-240 V

Voltage 2 (V): 380-415 V

Type of electric cable: Single phase

Frequency (Hz): 50/60 Hz

Power supply cable length: 120 cm

## Gas Connection

---

Gas Type: G20 Natural gas

Gas connection rating (W): 6000 W

Gas connection: Cilindrical

Other gas nozzles included:

G30 GPL Liquid gas

Other gas connections provided: Conical

## Accessories not included

---



### GRW

Wok support



### LGCN

Connecting Strip Built-in hobs, stainless steel, 475/495 mm



### TPK

Stainless steel grill plate to cook Teppanyaki dishes



### WOKGHU

Cast-Iron WOK Support



