



STL7224L

Product Family: Dishwashers

Commercial width: 60 cm

Commercial height: 82 cm

Installation: Fully-integrated

Third upper basket for cutlery

Motor: Single phase

EAN code: 8017709232375



Programs / Functions

No. of programmes: 5+5 quick programmes

Washing temperatures: 38°, 45°, 50°, 55°, 65°, 70° °C

Soak, Rapid 27', Crystal, ECO, Auto sensor 45-65, Ultraclean, ECO Quick, Delicate and Quick, Normal Quick, Strong and fast

Options

Energy saving option EnerSave,

Delay timer option: Up to 24 hours, with automatic soak

1/2 load FlexiZone option (varied distribution) , Options for tabs FlexiTabs, Quick Time option

Baskets

Basket colour: Grey

Basket components colour: Grey

Handle: In plastic with stainless steel insert on upper and lower basket

Upper Basket: With central fixed racks

Height adjustment of the upper basket: On three levels

Upper basket with EasyGlide System

Largest loadable dish in upper basket: 23,5 cm

Lower Basket: With double foldable rack

Lower basket with anti-drip inserts

Largest loadable dish in lower basket: 30 cm

Colour Inner Components: Blue anti drop inserts, Blue handles, Blue pastic plate for regulation second basket on three levels, Blue Planetarium

Technical Features

Controls: Electronic

Display type: 3 digit

Display: Delayed start, Programme time indicator, Time to end indication

Programme graphics: Symbols

Salt light indicator: Light

Rinse aid indicator: Light

End of cycle indicator: ActiveLight

Washing system: Planetarium

Third spray arm: Single

Water softener: With electronic setting

Turbidity sensor Aquatest

Flood protection system: Total Acquastop

Water supply: Single; cold/hot water max. 60°C - energysave with hot water up to 35%

Max water hardness: 100°fH;58°dH

Drying system: Natural condenser drying, with EnerSave automatic door opening system at the end of the cycle

Steam protection: In plastic

Tub material: Stainless steel

Filter: Stainless steel

Concealed heating element

Hinges: Self balancing, Sliding, FLEXIFIT

Min. and max. frontal panel weight: 2 - 11 kg

Adjustable feet: 7cm, from 820 to 890 mm

Insulation level: Top

Additional gaskets with stainless steel plate

Depth of dishwasher with open door (mm): 1168

Back feet adjustable from front

Top cover: In plastic

Performance / Energy Label

Number of place settings: 13
Energy efficiency class: A+++
Noise level: 42 dB(A) re 1pW
Energy consumption per cycle (kWh/cycle): 0.81 kWh
Water consumption per cycle (l/cycle): 8.5 litres
Annual energy consumption: 230 kWh/year
Annual water consumption: 2380 litres
Reference programme: ECO

Total cycle time of reference programme (min): 170 min
Energy consumption - stand by off mode: 0.02 W
Energy consumption - stand by on mode: 0.8 W
Duration of the stand by on mode (min): 5 min

Electrical Connection

Plug: (F;E) Schuko
Connected power: 1800 W
Current: 10 A
Voltage: 220-240 V
Type of connection: Single-phase

Frequency (Hz): 50 Hz
Power supply cable length: 140 cm

Accessories not included



KIT6CXF

Classic aesthetics stainless steel panel with 14 mm. handle. Can be fitted on the fully integrated dishwashers with Flexifit hinges. It is not possible to install it on the models with stainless steel panel



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



KITPL60B

Toe kick Kit in White colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



KITPL60N

Toe kick Kit in Black colour with adjustable height and deepness. Can be installed over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



KITPL60X

Toe kick Kit in Stainless Steel with adjustable height and deepness. Can be fitted over all the fully integrated and underbench models with variable fulcrum or flexifit hinges.



KITPLV2

Kit extension for dishwasher and washing machine: length mt. 2

