

TR103IBL

Cooker size: 100x60 cm

N. of cavities with energy label: 2 Heat source first cavity: Electric

Hob type: Induction

Type of main oven: Thermo-ventilated
Type of second oven: Fan assisted
Cleaning system main oven: Vapor Clean

EAN code: 8017709237349

Energy efficiency class first cavity: A Energy efficiency class, second cavity: B



Programs / Functions

No. of cooking functions: 8
Traditional cooking functions

Cleaning functions

Aesthetics

Colour: Black

Decoration / Special colour: --NA--

Aesthetics: Victoria Serie: --NA--

Collaborations: --NA--Design: Victoria Door: With frame

Upstand

Type of pan stands: Cast Iron Hob colour: Stainless steel

Command panel finish: Enamelled metal

Control knobs: Smeg Victoria Controls colour: Stainless steel Display: electronic 5 buttons Colour of buttons: Black No. of controls: 10 Serigraphy colour: Silver Handle: Smeg Victoria

Handle Colour: Brushed stainless steel

Glass type: Black Plinth: Anthracite Logo: assembled 50's

Logo position: Upstand+ Command panel Alternative colours available: Cream

Hob technical features

Total no. of cook zones: 5

Front left - Induction - single - 1.30kW - Booster 1.40kW - Ø 18.0 cm Rear left - Induction - single - 2.30kW - Booster 3.00kW - Ø 21.0 cm Central - Induction - single - 2.30kW - Booster 3.00kW - Ø 27.0 cm Rear right - Induction - single - 1.30kW - Booster 1.40kW - Ø 18.0 cm Front right - Induction - single - 2.30kW - Booster 3.00kW - Ø 21.0 cm

Main Oven Technical Features

No. of lights: 1
Fan number: 1

Net volume 1st cavity: 61 litres Gross volume, 1st cavity: 70 litres



Cavity material: Ever Clean enamel

No. of shelves: 4

Type of shelves: Metal racks

Light type: Halogen Light Power: 40 W

Cooking time setting: Start and Stop

Door opening: Side opening

Side opening door Removable door Full glass inner door

Total no. of door glasses: 3

No.of thermo-reflective door glasses: 1

Safety Thermostat

Cooling system: Tangential

Usable cavity space dimensions (HxWxD): 316x444x425 mm

Temperature control: Electro-mechanical Lower heating element power: 1200 W Upper heating element - Power: 1000 W

Grill elememt: 1700 W Large grill - Power: 2700 W

Circular heating element - Power: 2000 W

Grill type: Electric

Tilting grill



Options Main Oven

Timer

End of cooking acoustic alarm Minimum Temperature: 50 °C Maximum temperature: 260 °C

Second Oven Technical Features

Net volume, 2nd cavity: 84 litres Gross volume, 2nd cavity: 94 litres Cavity material: Ever Clean enamel

No. of shelves: 9

Type of shelves: Metal racks

No. of lights: 1 Light type: Halogen Light Power: 40 W

Door opening: Side opening

Side opening door Removable door Full glass inner door Removable inner door No. total door glasses: 2

No. thermo-reflective door glasses: 1

Safety Thermostat

Cooling system: Tangential

Usable cavity space dimensions (HxWxD): 605x375x375 mm

Temperature control: Electro-mechanical Circular heating element - Power: 2500 W

Options Auxiliary Oven

Minimum Temperature: 50 °C Maximum temperature: 245 °C

Third Oven Technical Features

Net volume, 3rd cavity: 36 litres Gross volume, 3rd cavity: 41 litres Cavity material: Ever Clean enamel

No. of shelves: 2

Type of shelves: Metal racks

No. of lights: 1 Light type: Halogen Light Power: 40 W Door opening: Flap down

Removable door Full glass inner door Removable inner door No. total door glasses: 3

No. of thermo-reflective door glasses: 1

Safety Thermostat

Cooling system: Tangential

Usable cavity space dimensions (HxWxD): 169x440x443 mm

Temperature control: Electro-mechanical

Large grill - Power: 2700 W

Grill type: Electric

Tilting grill

Options Third Oven

Minimum Temperature: 50 °C Maximum temperature: 260 °C

Accessories included for Main Oven & Hob

TOP Oven grid with back stop: 2

Grill mesh: 1 40mm deep tray: 1

Telescopic Guide rails, partial Extraction: 1

Accessories included for Secondary Oven

Oven grid with back stop: 4 Plate rack/warmer: 1



Accessories included for Third Oven

Oven grid with back and side stop: 1

40mm deep tray: 1

Electrical Connection

Electrical connection rating: 20000 W

Current: 54 mm Voltage: 220-240 V Voltage 2 (V): 380-415 V Frequency: 50 Hz

Power supply cable length: 150 cm

Terminal block: 5 poles

