

**Product fiche concerning the Commission Delegated Regulation (EU) No 65/2014 of 1 October 2013 and COMMISSION REGULATION (EU) No 66/2014 of 14 January 2014**

---

Supplier name or brand	SMEG
Product code	KSDD90VN-2
Annual Efficiency Consumption (AEC <sub>hood</sub> )	53 kWh/year
Energy efficiency class	A
Fluid Dynamic Efficiency (FDE <sub>hood</sub> )	30.5
Fluid Dynamic Efficiency class	A
Lighting Efficiency (LE <sub>hood</sub> )	40.2
Lighting Efficiency Class	A
Grease Filtering Efficiency	38.9 %
Grease Filtering Efficiency Class	G
Air Flow at minimum speed	230 m³/h
Air flow at maximum speed	500 m³/h
Air flow at boost speed	730 m³/h
Airbourne acoustical A-weighted sound Power Emission at minimum speed	42 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed	59 dB(A)
Airbourne acoustical A-weighted sound power emission at boost speed	66 dB(A)
Time increase factor	1.00
Energy Efficiency Index per first cavity	53.1
Measured air flow rate at best efficiency point	349 m³/h
Measured air pressure at best efficiency point	464 Pa
Measured electric power input at best efficiency point	147 W
Normal Power of the light system	6 W
Average illumination of the light on the cooking surface (E <sub>middle</sub> )	253
Sound power level at highest setting	59 dB(A)

26 April 2024