



DWAFI6314

Product Family: Dishwashers

Commercial width: 60 cm

Commercial height: 82 cm

Installation: Fully-integrated

Third upper basket for cutlery: 3, with Flexi third basket

Motor: Single phase

EAN code: 8017709220006



Programs / Functions

No. of programmes: 5+5 quick programmes

Washing temperatures: 38°, 50°, 55°, 65°, 70° °C

Soak, Rapid 27', ECO, Ultraclean, ECO Quick, Delicate and Quick, Daily Quick, Strong and fast, Intensive 65°, Normal ECO

Options

Delay timer option: 3-6-9 hours, with automatic soak

Quick Time option

Baskets

Basket colour: Grey

Basket components colour: Grey

Handle: In plastic with stainless steel insert on upper and lower basket

Upper Basket: With central fixed racks

Height adjustment of the upper basket: On three levels

Largest loadable dish in upper basket: 23,5 cm

Lower Basket: With double foldable rack

Lower basket with anti-drip inserts

Largest loadable dish in lower basket: 30 cm

Technical Features

Controls: Electronic

Programme graphics: Symbols

On/off indicator

Rinse aid indicator: Light

End of cycle indicator: Acoustic signal

Washing system: Orbital

Third spray arm: Single

Flood protection system: Total Acquastop

Water supply: Single; cold/hot water max. 60°C - energysave with hot water up to 35%

Max water hardness: 100°FH;58°dH

Drying system: Natural condenser drying

Steam protection: In plastic

Tub material: Stainless steel

Filter: Stainless steel

Concealed heating element

Hinges: Self balancing with fixed hinges

Min. and max. frontal panel weight: 2 - 7 kg

Adjustable feet: 7cm, from 820 to 890 mm

Insulation level: Medium

Additional gaskets with stainless steel plate

Back cover

Depth of dishwasher with open door (mm): 1146

Back feet adjustable from front

Top cover: In plastic

Performance / Energy Label

Number of place settings: 14 AU

Noise level: 47 dB(A) re 1pW

Water consumption per cycle (l/cycle): 9.6 litres

Annual energy consumption: 243 KWh/year

Reference programme: Normal ECO

Total cycle time of reference programme (min): 140 min

Duration of the stand by on mode (min): 5 min

Energy Label ex EU: Energy rating: 3,5 stars - Water rating: 5,5 stars

Electrical Connection

Plug: (I) Australia

Connected power: 1800 W

Current: 10 A

Voltage: 220-240 V

Type of connection: Single-phase

Frequency (Hz): 50 Hz

Power supply cable length: 140 cm

Accessories not included



KIT6CX

Classic aesthetics stainless steel panel with 14 mm. handle. Can be fitted on the fully integrated dishwashers.



KITGH

Kit glass holder. It has to be fitted on the first basket but only if there are foldable racks



KITPL60FABB

Toekick Kit in White colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPL60FABN

Toekick Kit in Black colour with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPL60FABX

Toekick Kit in Stainless Steel with adjustable height. Can be fitted over all the fully integrated and underbench models with Fixed Fulcrum. Can be installed also on the models with variable fulcrum or flexifit hinges.



KITPLV2

Kit extension for dishwasher and washing machine: length mt. 2

